



- CONDUCTOR : Compact round stranded annealed copper
 - CONDUCTOR SCREEN : Semiconducting cross-linked polyethylene
 - INSULATION : Cross-linked polyethylene (XLPE)
 - INSULATION SCREEN : Semiconducting cross-linked polyethylene
 - METALLIC SHIELD : Annealed copper wire with copper contact tape
 - SEPARATOR TAPE : Spunbond tape (Optional : water blocking tape)
 - OUTER SHEATH : Black polyethylene (Optional : Polyvinyl chloride (S12))
- CLASSIFICATION : Maximum Conductor Temperature
90 °C (Normal operation)
Maximum Conductor Temperature
250 °C (Short - circuit at 5 s maximum duration)
 - REFERENCE IEC 60228 & IEC 60502-2
 - AC TEST VOLTAGE : 42 Kv. For 5 minutes

SIZE core x mm ²	Nominal section area mm ²	Minimum number of wire No.	Diameter of conductor (Approx) mm	Thickness of conductor screen (Approx) mm	Thickness of insulation mm	Diameter over insulation (Approx) mm	Thickness of insulation screen (Approx) mm	Copper wire shield		Thickness of sheath mm	Overall diameter (Approx) mm	Maximum DC conductor resistance at 20 °C Ω/KM	Cable weight (Approx) Kg/Km	Standard packing m/R
								Number of wire	Diameter of wire mm					
1 x 50	50	6	8.33	0.5	8.0	25.5	0.5	20	0.8	2.0	34	0.3870	1370	500
1 x 70	70	12	9.73	0.5	8.0	27.5	0.5	20	0.8	2.0	35	0.2680	1620	500
1 x 95	95	15	11.45	0.5	8.0	28.5	0.5	20	0.8	2.1	37	0.1930	1930	500
1 x 120	120	18	12.95	0.5	8.0	30.0	0.5	20	0.8	2.1	39	0.1530	2210	500
1 x 150	150	18	14.27	0.5	8.0	32.0	0.5	25	0.9	2.2	40	0.1240	2590	500
1 x 185	185	30	15.98	0.5	8.0	33.0	0.5	30	1.03	2.2	42	0.0991	2990	500
1 x 240	240	34	18.47	0.5	8.0	35.5	0.5	30	1.03	2.3	43	0.0754	3710	500
1 x 300	300	53	20.68	0.5	8.0	38.5	0.5	30	1.03	2.4	44	0.0601	4370	500
1 x 400	400	53	23.39	0.5	8.0	40.5	0.5	30	1.03	2.5	50	0.0470	5260	500
1 x 500	500	53	26.67	0.5	8.0	44.0	0.5	30	1.03	2.6	54	0.0366	6440	250

C:Packing in coil.

D:Packing in drum.

